



# Safety Data Sheet(SDS)

## According to GHS

**Product name:** ABS filament

**Prepared by** GB/T 16483 and GB/T 17951

**Revision Date:** 2018.3.1

**SDS Number:** YS3D215001

**Initial date:** 2015.4.15

**Version:** 3.2

### Section 1 - Identification of the substance/preparation and of the company/undertaking

#### Product identifier

**Product name:** ABS luminous filament

#### Relevant identified uses of the substance or mixture and uses advised against

#### Details of the supplier of the safety data sheet

**Manufacture/Supplier :** Shenzhen Esun Industrial Co., Ltd.

**Address:** Wuhan University Building A403-I, No.6 Yuexing2Road,Nanshan District,  
Shenzhen, China

**Tel:** 135 3064 5059

**Emergency number :** 135 3064 5059

**E-mail :** cdm@brightcn.net

**Fax :** 2603 1982

**Further information obtainable from:**Shenzhen Esun Industrial Co.,Ltd

### Section 2 - Hazards Identification

	Min	Max
Flammability	1	0=Minimum
Toxicity	0	1=Low
Body Contact	2	2=Moderate
Reactivit	1	3=High
Chronic	2	4=Extreme

#### GHS classification

Not Applicable

#### Label elements:

#### GHS label elements

Not Applicable

#### SIGNAL WORD:

Not Applicable

**Product name: ABS filament**

**SDS Number: YS3D215001**

**Revision Date: 2018.3.1**

### **Section 3 –Composition/Information on Ingredients**

<b>Ingredient Name</b>	<b>CAS No.</b>	<b>EC No.</b>	<b>Content (%)</b>
ABS	9003-56-9	618-371-8	99
N,N'-Ethylenebis	110-30-5	203-755-6	0.5
Typical Antioxidant	31570-04-4	250-709-6	0.5

### **Section 4 - First Aid Measures**

#### **INGESTION**

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

#### **EYE**

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### **SKIN**

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

#### **Inhalation**

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

#### **Indication of any immediate medical attention and special treatment needed**

- Treat symptomatically.

### **Section 5 - Firefighting Measures**

#### **EXTINGUISHING MEDIA**

- Do NOT direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

#### **FIRE FIGHTING**

**Product name: ABS filament**

**SDS Number:YS3D215001**

**Revision Date: 2018.3.1**

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.

#### **FIRE/EXPLOSION HAZARD**

- Combustible solid which burns but propagates flame with difficulty.
- Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions).

#### **FIRE INCOMPATIBILITY**

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.as ignition may result

### **Section 6 –Accidental Release Measures**

#### **MINOR SPILLS**

- Generally not applicable

#### **MAJOR SPILLS**

- Generally not applicable

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **Section 7 - Handling and Storage**

#### **PROCEDURE FOR HANDLING**

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.

#### **SUITABLE CONTAINER**

- Multi-ply paper bag with sealed plastic liner or heavy gauge plastic bag.
- NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Check that all containers are clearly labelled and free from leaks.

**Product name: ABS filament**

**SDS Number:YS3D215001**

**Revision Date: 2018.3.1**

Packing as recommended by manufacturer.

### **STORAGE INCOMPATIBILITY**

- Avoid reaction with oxidising agents

## **Section 8 - Exposure Controls, Personal Protection**

### **EXPOSURE CONTROLS**

#### **Appropriate engineering controls**

For molten materials:

Provide mechanical ventilation; in general such ventilation should be provided at compounding/ converting areas and at fabricating/ filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten material. Keep dry!!

Processing temperatures may be well above boiling point of water, so wet or damp material may cause a serious steam explosion if used in unvented equipment.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.

#### **Personal protection**



#### **Eye and face protection**

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

#### **Skin protection**

See Hand protection below

#### **Hands/feet protection**

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

**Product name: ABS filament**

**SDS Number:YS3D215001**

**Revision Date: 2018.3.1**

Suitability and durability of glove type is dependent on usage.

**Body protection**

See Other protection below

**Other protection**

- Overalls.
- P.V.C. apron.
- Barrier cream.

**Section 9 - Physical and Chemical Properties**

**Information on basic physical and chemical properties**

<b>Odour</b>	Room temperature : Odorlessness Heating : Pungent odor
<b>Form</b>	Solid
<b>Melting Range (°C)</b>	No data
<b>Boiling Range (°C)</b>	No data
<b>Flash Point (°C)</b>	No data
<b>Decomposition Temp (°C)</b>	No data
<b>Autoignition Temp (°C)</b>	No data
<b>Upper Explosive Limit (%)</b>	No data
<b>Lower Explosive Limit (%)</b>	No data
<b>Volatile Component (%vol)</b>	No data
<b>Solubility in water (g/L)</b>	Insoluble in water
<b>p H (1% solution)</b>	No data
<b>p H (as supplied)</b>	No data
<b>Print Temp (°C)</b>	220-260
<b>Bed Temp(°C)</b>	90-110
<b>Density(g/cm<sup>3</sup>)</b>	1.04
<b>Heat Distortion Temp (°C,0.45MPa)</b>	78
<b>Melt Flow Index (g/10min)</b>	12 (220°C/10kg)
<b>Tensile Strength (MPa)</b>	43
<b>Elongation at Break (%)</b>	22
<b>Flexural Strength (MPa)</b>	66
<b>Flexural Modulus (MPa)</b>	2348
<b>IZOD Impact Strength (kJ/m<sup>2</sup>)</b>	19

**Section 10 - Stability and Reactivity**

**Reactivity**

See section 7

**Chemical stability**

- Unstable in the presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

**Section 11 - Toxicological Information**

**Information on toxicological affects**

**Acute Toxicity**

**LD/LC50 values relevant for classification**

No data.

**Primary irritant effect**

**On the skin**

No data.

**On the eyes**

No data.

**Inhaled**

No data.

**Sensitization:** No data.

**Section 12 - Ecological Information**

<b>Ingredient</b>	<b>Persistence: Water/Soil</b>	<b>Persistence: Air</b>	<b>Bioaccumulation</b>	<b>Mobility</b>
ABS	LOW	LOW	LOW	LOW
N,N'-Ethylenebis	No Data available	No Data available	No Data available	No Data available
Typical Antioxidant	No Data available	No Data available	No Data available	No Data available

**Section 13 - Disposal Considerations**

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse

**Product name: ABS filament**

**SDS Number:YS3D215001**

**Revision Date: 2018.3.1**

- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

#### **Section 14 - Transport Information**

##### **Labels Required**

Marine Pollutant: NO

**NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADR, IATA, IMDG,ADN**

#### **Section 15 - Regulatory Information**

##### **REGULATIONS**

The product needs to follow local regulations.

#### **Section 16 - Other Information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

\*\*\*End \*\*\*